

SPECIFICATIONS – No. 1060 Pump Island Display

- Width: 22-1/2" (26" over wheels – (29" including display tires)
- Depth: 22-1/2" (29" including display tires)
- Height: 45" (60" with tire in top cradle)
- Tubing: 1" OD x 18 gauge welded steel
- Top Tire Cradle: Formed steel tube, supported by brace strap each side.
- Front Toe: 1" wide x 11 gauge formed steel.
- Tee Connectors: Four pieces die-formed 12 gauge steel.
- Wheels: 6" OD x 1.50" semi-pneumatic tires on pressed steel or high impact polyolefin hub.
- Axle: 1/2" OD x 16 gauge welded steel tube, bright zinc chromate plated.
- Axle Cover: .706" OD x 19 gauge zinc plated tubular steel.
- Fasteners: Bright zinc plated; nuts are hex "Keps" with integral tooth type lockwashers.
- Finish: Bright zinc plated, with chromate conversion coating and final coat of clear lacquer.
- Packaging: Individually cartoned, KD, with illustrated assembly instruction sheet included. Shipping weight 16#. Exterior carton size: 42-5/8" x 10-3/8" x 2-3/4". Package qualifies for shipment by United Parcel Service.
- Availability: Stock -- no specific quantity purchase commitment required.